

## 3-SIDE TRIMMER BC 330

### Technical data

<b>Power, Single block / Multiple block</b>	220 / 600 books/h
<b>Book block untrimmed min. / max.</b>	107 x 152 mm / 305 x 330 mm // 4.21" x 5.98" / 12" x 12.99"
<b>Book block cut min. / max.</b>	105 x 148 mm / 303 x 326 mm // 4.13" x 5.82" / 11.93" x 12.83"
<b>Heat cut min. / max.</b>	2 mm / 91 mm // 0.078" / 3.58"
<b>Front cut min. / max.</b>	2 mm / 200 mm // 0.078" / 7.87"
<b>Foot cut min. / max.</b>	2 mm / 91 mm // 0.078" / 3.58"
<b>Book thickness min. / max.</b>	2 mm / 51 mm // 0.078" / 2.00" (for minimum book thickness - number of products >1.)
<b>Electric power consumption (apparent power)</b>	3.5 KVA
<b>Heat output</b>	11,946 BTU/h
<b>Weight // Weight with transport pallet</b>	1,230 kg / 2,712 lbs // 1,500 kg / 3,307 lbs
<b>Height</b>	1,580 mm / 62.20"
<b>Clamp pressure, min.</b>	200 daN / 440,92 lbs
<b>Clamp pressure, max.</b>	600 daN / 1322.76 lbs
<b>Knife thickness</b>	9.7 mm / 0.38"
<b>Knife grinding reserve, max.</b>	15 mm / 0.59"
<b>Static floor load</b>	500 daN/m <sup>2</sup> / 105 lbs/sqft
<b>Specific surface pressure</b>	8 daN/cm <sup>2</sup> / 116 lbs/sqin
<b>Dynamic surcharge</b>	20%
<b>Compressed-air requirement</b>	380 l/min.
<b>Hydraulic operating pressure</b>	16 - 150 bar
<b>Highest permissible hydraulic pressure</b>	200 bar
<b>Supply voltage (three-phase AC) 380V / 60Hz / fuse</b>	16 A
<b>Supply voltage (three-phase AC) 400V / 50Hz / fuse</b>	16 A
<b>Attention!</b>	
The wire cross section of the power supply to the machine must correspond to valid regulations in the country of use. The same applies to the plug connectors used.	