

# High-Speed Cutter N 155 AT HD

the programmable high performance model  
with automatic trim removal



## Description N 155 AT HD

Our model N 155 AT HD is the most-efficient model of this type of high-speed cutter featuring automatic waste disposal during the cutting process.

The High-Speed Cutter POLAR N 155 is mainly used in the large-size range. Formats up to a diagonal of 1,550 mm can be easily handled and turned in the high-speed cutter. Cutting material with larger formats can only be turned on the front table. The High-Speed Cutter can be upgraded with peripheral equipment (lift, jogger, buffer, transport grippers, loading and unloading system) to a cutting system.

## Customer benefits

- Extended operating life of the knife as well as faster knife change thanks to POLAR OptiKnife with knife fine adjustment in the lower dead end
- The automatic trim removal can increase your productivity up to 30%
- Shortest make ready times thanks to intuitive cutting program generation via block programming or even Compucut
- Greatest cutting accuracy due to the POLAR-Positioning-System DPS with a mechanical positioning accuracy of 1/100 mm
- Highly reliable in daily use and long lifespan as a result of the stability of the one-piece machine frame, knife drive with worm gear drive and compact closed hydraulic system

## Technical data

Cutting width	1,550 mm   61.02 in
Feeding depth	1,550 mm   61.02 in
Loading height max.	165 mm   6.50 in
Safety clamp pressure	30 daN   66 lbs
Clamp pressure, min	150 daN   331 lbs
Clamp pressure, max	6,000 daN   13,228 lbs
Backgauge speed on return way (0 - ...)	300 mm/sec 11.81 in/sec
Knife speed	45 cycles/min
Smallest cut, automatically, without false plate	35 mm   1.38 in
Smallest cut, automatically, with false plate	120 mm   4.72 in

Further technical data are available for download on our website.

Edition: 01.2024 \ Subject to technical alterations.

# High-Speed Cutter N 155 PRO HD

the programmable high performance model  
with a capacitive 21.5" Touch-Screen display



## Description High-Speed Cutter N 155

The programmable high performance model with a capacitive 21.5" Touch-Screen display and real image preview is ideal for high-end applications - thanks to job specific programmable parameter, label and distortion correction as well as an extended range of options.

The High-Speed Cutter POLAR N 155 is mainly used in the large-size range. Formats up to a diagonal of 1,550 mm can be easily handled and turned in the high-speed cutter. Cutting material with larger formats can only be turned on the front table. The High-Speed Cutter has extensive features in the standard equipment already which can increase the productivity up to 20%. The High-Speed Cutter can be upgraded with peripheral equipment (lift, jogger, buffer, transport grippers, loading and unloading system) to a cutting system.

## Customer benefits

- Extended operating life of the knife as well as faster knife change thanks to POLAR OptiKnife with knife fine adjustment in the lower dead end
- High productivity by a great number of programmable additional functions
- Shortest make ready times thanks to intuitive cutting program generation via block programming or even Compucut
- Greatest cutting accuracy due to the POLAR-Positioning-System DPS with a mechanical positioning accuracy of 1/100 mm
- Highly reliable in daily use and long lifespan as a result of the stability of the one-piece machine frame, knife drive with worm gear drive and compact closed hydraulic system

## Technical data

Cutting width	1,550 mm   61.02 in
Feeding depth	1,550 mm   61.02 in
Loading height max.	165 mm   6.50 in
Safety clamp pressure	30 daN   66 lbs
Clamp pressure, min	150 daN   331 lbs
Clamp pressure, max	6,000 daN   13,228 lbs
Backgauge speed on return way (0 - ...)	300 mm/sec 11.81 in/sec
Knife speed	45 cycles/min
Smallest cut, automatically, without false plate	35 mm   1.38 in
Smallest cut, automatically, with false plate	120 mm   4.72 in

Further technical data are available for download on our website.

Edition: 01.2024 \ Subject to technical alterations.